

Q&A and Counting k -mers Example

Q&A

Counting k -mers

Counting k -mers

A common operation in computational genomics is finding the number of k -mers in a DNA sequence. This is the number of all possible substrings of length k in a given sequence.

Counting k -mers

A common operation in computational genomics is finding the number of k -mers in a DNA sequence. This is the number of all possible substrings of length k in a given sequence. For example, the sequence

AAGAGT

has the following 2-mers:

Counting k -mers

A common operation in computational genomics is finding the number of k -mers in a DNA sequence. This is the number of all possible substrings of length k in a given sequence. For example, the sequence

AAGAGT

has the following 2-mers:

AA

Counting k -mers

A common operation in computational genomics is finding the number of k -mers in a DNA sequence. This is the number of all possible substrings of length k in a given sequence. For example, the sequence

AAGAGT

has the following 2-mers:

AA

AG

Counting k -mers

A common operation in computational genomics is finding the number of k -mers in a DNA sequence. This is the number of all possible substrings of length k in a given sequence. For example, the sequence

AAGAGT

has the following 2-mers:

AA

AG

GA

Counting k -mers

A common operation in computational genomics is finding the number of k -mers in a DNA sequence. This is the number of all possible substrings of length k in a given sequence. For example, the sequence

AAGAGT

has the following 2-mers:

AA

AG (twice)

GA

Counting k -mers

A common operation in computational genomics is finding the number of k -mers in a DNA sequence. This is the number of all possible substrings of length k in a given sequence. For example, the sequence

AAGAGT

has the following 2-mers:

AA

AG (twice)

GA

GT

Counting k -mers

A common operation in computational genomics is finding the number of k -mers in a DNA sequence. This is the number of all possible substrings of length k in a given sequence. For example, the sequence

AAGAGT

has the following 2-mers:

AA

AG (twice)

GA

GT

And the following 3-mers:

Counting k -mers

A common operation in computational genomics is finding the number of k -mers in a DNA sequence. This is the number of all possible substrings of length k in a given sequence. For example, the sequence

AAGAGT

has the following 2-mers:

AA

AG (twice)

GA

GT

And the following 3-mers:

AAG

Counting k -mers

A common operation in computational genomics is finding the number of k -mers in a DNA sequence. This is the number of all possible substrings of length k in a given sequence. For example, the sequence

AAGAGT

has the following 2-mers:

AA

AG (twice)

GA

GT

And the following 3-mers:

AAG

AGA

Counting k -mers

A common operation in computational genomics is finding the number of k -mers in a DNA sequence. This is the number of all possible substrings of length k in a given sequence. For example, the sequence

AAGAGT

has the following 2-mers:

AA

AG (twice)

GA

GT

And the following 3-mers:

AAG

AGA

GAG

Counting k -mers

A common operation in computational genomics is finding the number of k -mers in a DNA sequence. This is the number of all possible substrings of length k in a given sequence. For example, the sequence

AAGAGT

has the following 2-mers:

AA

AG (twice)

GA

GT

And the following 3-mers:

AAG

AGA

GAG

AGT